

SI-7908HCSUS



**2 seconds installation
SATA HDD docking unit**

Introduction

SI-7908HCSUS direct inserting all 3.5" or 2.5" SATA HDD into docking unit, 2 BAY USB2.0 HUB for your USB devices. The 8 IN 1 Cardreader function for SD/MMC/MS and so on. The e-SATA port transfer rate up to 3Gbps connect your HDD.

Features

- All 3.5"/2.5" SATA HDD compatible
- USB2.0 HUBX2
- 8 IN 1 Cardreader for SD/MMC/MS and so on
- With USB & eSATA interface
- Compatible with 1.5Gbps & 3.0Gbps SATA HDD
- Compact size docking design
- Power adaptor
- Patent design for HDD depart from docking unit
- Power LED indicate
- Access LED indicate

Package contents

Docking unit
DC adaptor
eSATA cable x1
USB cable x1
Manual x1

Hardware installation

TOP



1. Push button to release HDD from SATA connector
2. Button - 3, For 2.5" HDD - 4, For 3.5" HDD
5. Power and Access LED

BACK




Disk Installation



Install 2.5" HDD

Install 3.5" HDD



Patent design for HDD depart from docking unit

FCC and CE Radiation Norm

FCC

This equipment has been tested and found to comply with limits for Class B digital device pursuant to Part 15 of Federal Communications Commission (FCC) rules.

CE

This equipment has been tested and found to comply with the limits of the European Council Directive on the approximation of the law of the member states relating to electromagnetic compatibility (89/336/EEC) according to EN 55022 Class B.

FCC and CE Compliance Statement

These limits are designed to provide reasonable protection against frequency interference in residential installation. This equipment generates, uses and can radiate radio frequency energy, and if not installed or used in accordance with the instructions, may cause harmful interference to radio communication. However, there is no guarantee that interference will not occur in television reception, which can be determined by turning the equipment off and on. The user is encouraged to try and correct the interference by one or more of the following measures:

- ✦ Reorient or relocate the receiving antenna
- ✦ Increase the separation between the equipment and the receiver
- ✦ Connect the equipment into an outlet on a circuit different from that to which the receiver is connected to

CAUTION!

The Federal Communications Commission warns the user that changes or modifications to the unit not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.