

# SI-7928SUSJ



## 2 BAY HDD DOCKING STATION

### Introduction

SI-7928SUSJ direct inserting 2 bay All 3.5" or 2.5" SATA hard drives into docking unit. The design are simply and easy to install and use hard drives.

### Features

- All 2.5" or 3.5" SATA HDD compatible
- USB 2.0 transfer rate up to 480Mbps
- eSATA transfer rate up to 3.0Gbps, eSATA port Priority
- Compact size docking design
- 12V/5V 3A power adaptor
- Patent design for HDD depart from docking unit
- Power LED indicate
- Access LED indicate

### Package contents


Docking unit  
12V/5V 3A DC adaptor  
eSATA cable x2 (SI-7928SUSJ)  
USB cable x1  
Manual x1

### 2 Disk Installation



For 2.5" SATA HDDs

For 3.5" SATA HDDs



Patent design for HDD depart from docking unit

### FCC and CE Radiation Norm

#### FCC

This equipment has been tested and found to comply with limits for Class B digital device pursuant to Part 15 of Federal Communications Commission (FCC) rules.

#### CE

This equipment has been tested and found to comply with the limits of the European Council Directive on the approximation of the law of the member states relating to electromagnetic compatibility (89/336/EEC) according to EN 55022 Class B.

#### FCC and CE Compliance Statement

These limits are designed to provide reasonable protection against frequency interference in residential installation. This equipment generates, uses and can radiate radio frequency energy, and if not installed or used in accordance with the instructions, may cause harmful interference to radio communication. However, there is no guarantee that interference will not occur in television reception, which can be determined by turning the equipment off and on. The user is encouraged to try and correct the interference by one or more of the following measures:


- ✦ Reorient or relocate the receiving antenna
- ✦ Increase the separation between the equipment and the receiver
- ✦ Connect the equipment into an outlet on a circuit different from that to which the receiver is connected to

#### CAUTION!

The Federal Communications Commission warns the user that changes or modifications to the unit not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

### Hardware installation

#### 1 TOP



1. Push button to release HDD from SATA connector
2. For 2.5" HDD
3. For 3.5" HDD
4. Power and Access LED Button

#### 2 BACK

