



SSI Computer Corp.
OEM / ODM Design & Manufacturer

SI-110USJ3-5G

Specification



ITEM	SPEC	SPEC IN CHINESE
Model No.	SI-110USJ3-5G	SI-110USJ3-5G
Certifications	CE、FCC、RoHS compliance	符合 CE、FCC、RoHS 規範
Color	Black	黑色
Material	High quality metal for optimized heat dissipation	機身採用高質感全鋁材質,提升散熱效能
HDD Type	3.5" SATA I/II/III hard drives compatible	適用 3.5 吋 SATAI/II/III 硬碟
HDD Capacity	Up to 4TB/6Gbps HDD is supported	可以支持單顆 4TB/6Gbps 硬碟
Interfaces	1 x USB3.0 (Max.5Gpbs) 1 x eSATA (Max.6Gpbs) 2 x 1394B (Max.800Mpbs) 1 x 1394A (Max.400Mpbs)	1 x USB3.0 (理想值 5Gpbs) 1 x eSATA (理想值 6Gpbs) 2 x 1394B (理想值 800Mpbs) 1 x 1394A (理想值 400Mpbs)
Tray less	Support	支援
Screw less	Support	支援
Plug & Play	Support	支援
Sleep Mode	USB3.0 & 2.0 & eSATA & 1394A & 1394B sleep function: Disconnect the cable, the HDD will sleep function	USB3.0 & 2.0 & eSATA & 1394A & 1394B 休眠功能： USB: 1.PC 休眠、安全移除、拔掉 Cable、HDD 進入休眠 2. 無待機休眠功能 eSATA: 1.安全移除、待機休眠、HDD 無休眠功能 2. PC 休眠, 拔掉 Cable、HDD 休眠

ITEM	SPEC	SPEC IN CHINESE
		1394B : 1. PC 休眠、安全移除、拔掉 Cable、HDD 進入休眠功能 2.待機休眠·無休眠功能
LED Indicator	<ul style="list-style-type: none"> ● Power LED Blue for power on ● HDD status LED Red flashing for HDD access 	<ul style="list-style-type: none"> ● 電源指示燈 電源開啟以藍燈指示 ● 硬碟狀態燈 讀寫硬碟時以紅燈閃爍指示
Features	<ul style="list-style-type: none"> ● High capacity data storage ● Quick HDD installation ● Driver free ● Plug & play 	<ul style="list-style-type: none"> ● 高容量的資料儲存與傳輸工具 ● 快速硬碟安裝 ● 免驅動程式,隨插即用 ● 支持硬盤隨插即用
Environment	<p>Operating Temperature: 5°C ~ 35°C</p> <p>Operating Humidity: 20%RH ~ 80%RH</p> <p>Storage Temperature: -20°C ~ 50°C</p> <p>Storage Humidity: 20%RH ~ 80%RH</p>	<p>適用操作溫度: 5°C ~ 35°C</p> <p>適用操作濕度: 20%RH ~ 80%RH</p> <p>適用保存溫度: -20°C ~ 50°C</p> <p>適用保存濕度: 20%RH ~ 80%RH</p>
System Requirements (PC)	<p>USB3.0 (USB2.0/USB1.1) USB3.0 & 2.0 & eSATA & 1394A & 1394B: Windows XP/Vista/7/8</p>	<p>USB3.0 (USB2.0/USB1.1) USB3.0 & 2.0 & eSATA & 1394A & 1394B: Windows XP/Vista/7/8</p>
System Requirements	<p>USB3.0 & 2.0 & eSATA & 1394A & 1394B (USB2.0/1.1): Mac OS 10.5 or above</p>	<p>USB3.0 & 2.0 & eSATA & 1394A & 1394B (USB2.0/1.1): Mac OS 10.5 或更高版本</p>

ITEM	SPEC	SPEC IN CHINESE
(Mac)		
System Requirements (Linux)	USB3.0 & 2.0 & eSATA & 1394A & 1394B (downwards Compatible with USB1.1): Linux Kernel 2.6.31 or above	USB3.0 & 2.0 & eSATA & 1394A & 1394B (向下相容 USB1.1): Linux Kernel 2.6.31 或更高版本
Power Supply	Input: AC 100-240V, 50Hz/60Hz Output: DC+12V/3A	Input: AC 100-240V, 50Hz/60Hz Output: DC+12V/3A
Dimension	201mm x 145mm x 38mm	201mm x 145mm x 38mm