

SI-1119U31PV

Specification



Revision Notice

Rev.	Date	Description
1.0	Mov.13.2020	Initial release.

TABLE OF CONTENTS

1. Appearance	4
2. Specification.....	4
3. Features	4
4. Operating System Support	5
5. Power & Accessories	5

1. Appearance



2. Specification

- A 1 x USB Type-C cable.
- B 1 x HDMI Port.
- C 1 x VGA Port
- D 1 x M-Key M.2 SSD socket (built-in).

3. Features

- A High-strength ABS plastic.
- B Dimensions: 68 x 61 x 15mm.
- C With the USB Type-C DisplayPort Alternate Mode supporting
- D HDMI port for Support 4K@30Hz HD video.
- E VGA supports 1080p@60Hz output
- F Simultaneously display via HDMI and VGA outputs.
- G Supports 1 x M.2 NVMe SSD transfer speed up to 1000MB/s.
And support compatible B+M Key M.2 SATA SSD transfer speed up to 6Gbps/s.
Applicable SSD to sizes 2242 Only.
- H USB Gen2 type-C Cable supports 10Gbps to Host,
backward compatible with USB3.0 and USB2.0 (only for M.2 SSD function)
- I Plug & play, no additional drivers required.
- J Bus powered. Does not need an external power supply.

4. Operating System Support

- A. Mac OS X 10.14.4 and future releases.
- B. Windows XP, 7 SP1 32 and 64 bit, Windows 8/8.1 32 and 64 bit, Windows 10 32 and 64 bit and future releases.

5. Environment

- A. Operating Temperature: 5°C ~ 55°C
- B. Operating Humidity: 20%RH ~ 80%RH
- C. Storage Temperature: -20°C ~ 50°C
- D. Storage Humidity: 20%RH ~ 80%RH

6. Power & Accessories

- A. Retail Color Box x 1.
- B. Quick Start Guide document x 1.