



SI-120RSUS3

Specification





VERSION	DATE	NOTE	Modified By
V0.9	2016.12.19	變更 FW 版本，顯示客人產品名稱	黃德华

Detail Spec

Item	Spec	繁體中文	備註(粗體)或參考寫法
Model No.	120RSUS3	120RSUS3	
Certifications	CE、FCC、RoHS compliance	符合 CE、FCC、RoHS 規範	
Color	Black	黑色	
Material	High quality metal(iron) for optimizing heat dissipation	機身採用高質感全鐵材質, 提升散熱效能	◇
HDD Type	2 x 3.5" SATA I/II/III hard drives are compatible	適用 2 顆 3.5 吋 SATA I/II/III 硬碟	
HDD Capacity	1TB - 8TB per HDD is supported	支持 1TB - 8TB 硬碟	
Interface	1 x USB3.1 type C (Max. 10Gbps)	1 x USB3.1 type C (理想值 10 G Gbps)	◇
Tray less	Support	支援	
Screwless	Support	支援	
Hot Swappable	Support	支援	
Plug & Play	Support	支援	
Chipset	ASM1352R + ASM1542	ASM1352R + ASM1542	
RAID Mode	STANDARD、STRIPING、MIRRORING、COMBINE	STANDARD、STRIPING、MIRRORING、COMBINE	
RAID Setting	Hardware	硬體設置	
Sleep Mode	USB3.1 PC/MAC sleep function :1. PC dormancy, safe	USB3.1 休眠功能:	

Item	Spec	繁體中文	備註(粗體)或參考寫法
	removal, remove Cable => HDD dormancy	PC/MAC 休眠、安全移除、拔掉 Cable =>HDD 休眠	
Rebuild	MIRRORING Support	MIRRORING	
FAN	70*70*15mm FAN	70*70*15mm 風扇 X1	
LED Indicator	<ul style="list-style-type: none"> ● POWER Indicator Light Blue light: Power is on. ● HDD indicator: Red light: the red light while HDD isn't recognized; Blue light: the blue light flashes while reading and writing, twinkles slowly in Rebuilding mode. 	<ul style="list-style-type: none"> ● 電源指示燈 藍燈：電源開啟以藍燈指示。 ● 硬盤指示燈： 紅燈：沒有檢到硬碟，紅燈長亮； 藍燈：讀/寫硬碟時藍燈閃爍，Rebuild 時，藍燈慢閃。 	
Features	<ul style="list-style-type: none"> ● Support up to 2 x 3.5"SATA HDDs ● Tool-free and tray-less design ● Multi-function LED indicators ● interface including :USB 3.1 	<ul style="list-style-type: none"> ● 支援 2 個 3.5 "SATA 硬碟 ● 隨拆即用抽取式硬碟安裝設計 ● 多功能 LED 顯示 ● 支援高速傳輸介面:USB 3.1 	
Environment	<ul style="list-style-type: none"> ● Operating Temperature: 5°C ~ 35°C ● Operating Humidity: 20%RH ~ 80%RH ● Storage Temperature: -20°C ~ 50°C ● Storage Humidity: 20%RH ~ 80%RH 	<ul style="list-style-type: none"> ● 適用操作溫度：5° C ~ 35° C ● 適用操作濕度：20%RH ~ 80%RH ● 適用保存溫度：-20° C ~ 50° C ● 適用保存濕度：20%RH ~ 80%RH 	
System Requirements (PC)	USB 3.1 (USB 3.0/ 2.0/1.1)(Win 8 /10 Support USB 3.1) Windows 8.1+ASM1142 USB 3.1 Host USB 3.0 (USB2.0/ 1.1) Windows 7/8/10	USB 3.1 (USB 3.0/ 2.0/1.1) (僅在 Win 8/10 下支援 USB 3.1) Windows 8.1+ASM1142 USB 3.1 Host USB 3.0 (USB 2.0/1.1) Windows 7/8/10	
System Requirements (Mac)	USB 3.0 (USB 1.1) Mac OS 10.5 or above * Mac supportS capacity more than 2TB	USB 3.0 (USB 1.1) Mac OS 10.5 或更高版本 * Mac 系統可支援大於 2TB 的	



Item	Spec	繁體中文	備註(粗體)或參考寫法
Dimension	221.35*130*115mm (Without feet)	221.35*130*115mm(不含腳墊高度)	
Accessories	120RSUS3.1 (hard drives are not included) USB3.1 cable(A to C 100cm) x 1 Power Cable x 1 User manual x 1	120RSUS3.1 (不含硬碟) USB 3.1 傳輸線 (A to C 100cm) x 1 電源線 x 1 使用手冊 x 1	
FW Change List			
Number	Date	FW Version	Note
1	2016-12-19	161028_B5_20_40.bin	