

SI-2422TB3

Specification



Revision Notice

R.1.0 2018.08.15

Initial release

TABLE OF CONTENTS

1. Appearance	4
2. Specification	4
3. Features	5
4. Operating System Support	5
5. Power & Accessories	5

1. Appearance



2. Specification

- A. TBT3 x2
- B. DisplayPort 1.2 x1
- C. M.2 M-key socket x4 (PCIe 3.0 x1)

3. Features

- A. All metal housing.
- B. Compact size 195 x 120 x 20 mm.
- C. Supports 2 x thunderbolt3 40Gbps.
- D. Thunderbolt3 ports support PD 5V@3A 15W power source.
- E. 1 x DisplayPort1.2 for 4K@60Hz output.
- F. 4x M.2 PCIe NVMe SSD inside.
- G. Each SSD transfer rate up to 750MB/s.
- H. Build soft-raid0 can reach to 2500MB/s.
- I. 1 quiet Fan for better cooling performance.

4. Operating System Support

- A. Mac OS X 10.12.x and future releases.
- B. Windows10 32 and 64 bit and future releases.

5. Power & Accessories

- A. Including Thunderbolt cable, L=70cm
- B. External 12V 6A power adapter
- C. User manual x1.
- D. Retail Color Box x1.