

SI-4203CFEx

Specification



Revision Notice

Rev.	Date	Description
1.0	Jan.14.2021	Initial release.
1.0		

TABLE OF CONTENTS

1. Appearance.....	4
2. Specification.....	4
3. Features.....	4
4. Operating System Support.....	5
5. Environment.....	5
6. Power & Accessories.....	5

1. Appearance



2. Specification

- A. 1 x USB3.2 Gen.2 Type-C upstream.
- B. 1 x CFExpress (type-B).
- C. 1 x LED for power indicator.

3. Features

- A. High quality aluminum body for optimized heat dissipation.
- B. Dimensions: 51.40x45.00x12.00mm
- C. Functional LED power indicator.
- D. USB3.2 Gen2 Type-C Female connector supports 10Gbps to Host, backward compatible with USB3.0 and USB2.0.
- E. Supports 1 x CFExpress type-B Card super speed up to 950MB/s. Support Type-C Smartphones with OTG function.
- F. Plug & play, automatically installs drivers.
- G. Bus powered. Does not need external power.

4. Operating System Support

- D. Mac OS X 10.14.4 and future releases.
- E. Windows XP, 7 SP1 32 and 64 bit, Windows 8/8.1 32 and 64 bit, Windows 10 32 and 64 bit and future releases.

5. Environment

- F. Operating Temperature: 5°C ~ 55°C
- G. Operating Humidity: 20%RH ~ 80%RH
- H. Storage Temperature: -20°C ~ 50°C
- I. Storage Humidity: 20%RH ~ 80%RH

6. Power & Accessories

- A. Retail Color Box x 1.
- B. USB Cable: USB3.2 Gen.2 Type-C to Type-C 0.5 Meter x 1PCS.