

SI-6831US31C_IP67

Specification



Revision Notice


R.1.0 2019.10.09

Second release edition.

TABLE OF CONTENTS

1. Appearance.....	4
2. Specification.....	4
3. Features.....	4
4. Operating System Support.....	5
5. Power & Accessories.....	5

1. Appearance



2. Specification

- A. 1 x USB3.1 Gen.2 Type-C port.
- B. 1 x M-Key M.2 PCIe NVMe SSD socket (built-in).

3. Features

- A. High quality aluminum body for optimized heat dissipation.
- B. Dimensions: 105.00x45.00x14.00 mm.
- C. Pass army design with IP67 water/dust resistance, 1M drop tested.
- D. Functional LED power indicator.
- E. USB3.1 Gen2 type-C captive cable supports 10Gbps to Host, backward compatible with USB3.0 and USB2.0.
- F. Supports 1 x M.2 NVMe SSD transfer speed up to 1000MB/s. Applicable SSD to sizes 2242/ 2260/ 2280.

4. Operating System Support

- A. Mac OS X 10.14.4 and future releases.
- B. Windows XP, 7 SP1 32 and 64 bit, Windows 8/8.1 32 and 64 bit, Windows 10 32 and 64 bit and future releases.

5. Power & Accessories

- A. Retail Color Box x 1.
- B. USB 3.1 Gen 2 Type A to Type C Cable (E-Mark or without E-Mark) 0.5 Meter. (option)
- C. USB 3.1 Gen 2 Type C to Type C Cable (E-Mark or without E-Mark) 0.5 Meter. (option)
- D. Quick Start Guide document x 1.