

# SI-7927US31C-D Dock

## Specification





## Revision Notice

<b>Rev.</b>	<b>Date</b>	<b>Description</b>
1.0	Dec.14.2021	Initial release.
1.0		



---

## TABLE OF CONTENTS

1. Appearance.....	4
2. Specification.....	4
3. Features.....	5
4. Operating System Support.....	5
5. Environment.....	5
6. Power & Accessories.....	5

## 1. Appearance



## 2. Specification

- A. 1 x USB3.2 Gen.2 Type-C port.
- B. 1 x DC-Jack port.
- C. 1 x Power push Switch.
- D. 1 x Clone selection switch.
- E. 1 x M-Key M.2 PCIe NVMe SSD socket (built-in).
- F. 1 x SATA 7+15 socket(built-in).

### 3. Features

- A. High-strength ABS plastic.
- B. Dimensions: 134.75x94.45x68.95mm.
- C. Functional LED copy capacity status indicator, NVMe and SATA HDD/SSD status indicator and PC mode or duplicator mode status indicator.
- D. USB3.2 Gen2 type-C supports 10Gbps to Host, backward compatible with USB2.0 and USB1.1.
- E. Supports NVMe SSD transmit data speed for SATA port can reach 6Gbps or SATA SSD transmit data speed for NVMe port can reach 10Gbps.
- F. Support Independent Clone system operation without host computer. Clone without any driver, easy to operate.
- G. Clip Applicable SSD to sizes 2242/ 2260/ 2280.

### 4. Operating System Support

- A. Mac OS X 12.0.x and future releases.
- B. Windows 8/8.1/10 32 and 64 bit and future releases.

### 5. Environment

- A. Operating Temperature: 5°C ~ 55°C
- B. Operating Humidity: 20%RH ~ 80%RH
- C. Storage Temperature: -20°C ~ 50°C
- D. Storage Humidity: 20%RH ~ 80%RH

### 6. Power & Accessories

- A. Retail Color Box x 1.
- B. Quick Start Guide document x 1
- C. Power Supply: External universal Power adaptor x 1 ( 12V/4A )
- D. USB 3.1 Gen 2 Type C to Type C Cable (no e-mark) 0.5 Meter. (Option)