



## SI-7928USJ3-D Specification





| ITEM                   | SPEC  | SPEC IN CHINESE  |
|------------------------|---|--|
| <b>Model No.</b>       | <b>SI-7928USJ3-D</b>  | <b>SI-7928USJ3-D</b>   |
| <b>Certifications</b>  | CE、FCC、RoHS compliance  | 符合 CE、FCC、RoHS 規範  |
| <b>Color</b>           | Black   | 黑色   |
| <b>Material</b>        | Stylish plastic design  | 機身採用高質感塑膠材質  |
| <b>HDD Type</b>        | 3.5" SATA I/II/III hard drives compatible<br>2.5" SATA I/II hard drives/SSD compatible                                      | 適用 3.5 吋 SATA I/II/III 硬碟<br>適用 2.5 吋 SATA I/II 硬碟/SSD   |
| <b>HDD Capacity</b>    | Up to 2TB per HDD is supported<br>2 bay SATA HDD compatible   | 最高支持 2TB 硬碟<br>能夠同時使用 2 個的 SATA 硬碟   |
| <b>Interfaces</b>      | 1 x USB2.0 (Max. 480Mbps)<br>1 x e-SATA (Max. 3Gbps)  | 1 x USB2.0 (理論值最高 480Mbps)<br>1 x e-SATA (理論值最高 3Gbps)   |
| <b>Tray less</b>       | Support   | 支援   |
| <b>Screw less</b>      | Support   | 支援   |
| <b>Hot Swappable</b>   | Support   | 支援   |
| <b>Plug &amp; Play</b> | Support   | 支援   |
| <b>Duplicator</b>      | Stand alone<br>Sector to sector copy<br>File to file copy (software needed)<br>Copy rate at 84~102 MB/s                     | 能夠獨立操作不需要電腦<br>磁區對磁區的複製<br>檔對檔的複製 (需要軟體支援)<br>複製速度可以達到 84~102MB/s                                    |
| <b>LED Indicator</b>   | <ul style="list-style-type: none"><li>● Power LED<br/>Blue for power on</li><li>● PC/DUP LED<br/>Blue for PC mode</li></ul> | <ul style="list-style-type: none"><li>● 電源指示燈<br/>電源開啟以藍燈指示</li><li>● 模式指示燈<br/>PC 模式以藍燈指示</li></ul> |



| ITEM                       | SPEC   | SPEC IN CHINESE   |
|----------------------------|--|---|
|                            | <p>Red for DUP mode</p> <ul style="list-style-type: none"> <li>● HDD State LED</li> </ul> <p>Blue for HDD detected</p> <p>Red flashing for HDD access</p> <ul style="list-style-type: none"> <li>● 4 phases state LED</li> </ul> <p>4 blue lights back and forth flashing for HDD access</p> <p>Single blue light for copying/all blue lights for copy complete</p>  | <p>對拷模式以紅燈指示</p> <ul style="list-style-type: none"> <li>● 硬碟狀態燈</li> </ul> <p>硬碟偵測完成以藍燈指示</p> <p>讀寫硬碟時以紅燈閃爍指示</p> <ul style="list-style-type: none"> <li>● 4 顆階段性指示燈</li> </ul> <p>讀寫硬碟時以 4 顆藍燈來回閃爍指示</p> <p>正在複製以單個藍燈閃爍指示, 複製完成以 4 顆藍燈指示</p>                     |
| <b>Features</b>            | <ul style="list-style-type: none"> <li>● Support 2 x 2.5"/3.5" SATA HDDs</li> <li>● Easily copy any data from the HDD without PC required</li> <li>● 1:1 cloning of sectors from the source HDD to the object HDD</li> <li>● Interface with 4 phase LED display the rate of clone progress</li> <li>● Tool-free and tray-less design</li> <li>● Multi-function LED indicators</li> <li>● Versatile interface including e-SATA, and USB2.0</li> </ul> | <ul style="list-style-type: none"> <li>● 支援 2 個 2.5"/3.5" SATA 硬碟</li> <li>● 不需電腦即可完整複製硬碟的資料</li> <li>● 支援 1:1 從來源硬碟複製到目標硬碟</li> <li>● 4 顆階段性指示燈可以顯示複製的進度</li> <li>● 隨拆即用插拔式硬碟安裝設計, 無需螺絲固定</li> <li>● 多功能 LED 顯示</li> <li>● 支援多種高速傳輸介面: e-SATA, USB2.0</li> </ul> |
| <b>Environment</b>         | <p>Operating Temperature: 5°C ~ 35°C</p> <p>Operating Humidity: 20%RH ~ 80%RH</p> <p>Storage Temperature: -20°C ~ 50°C</p> <p>Storage Humidity: 20%RH ~ 80%RH</p>  | <p>適用操作溫度: 5°C ~ 35°C</p> <p>適用操作濕度: 20%RH ~ 80%RH</p> <p>適用保存溫度: -20°C ~ 50°C</p> <p>適用保存濕度: 20%RH ~ 80%RH</p>   |
| <b>System Requirements</b> | <p>e-SATA: Windows XP/Vista/7/8</p> <p>USB2.0 (USB1.1): Windows XP/Vista/7/8</p>   | <p>e-SATA: Windows XP/Vista/7/8</p> <p>USB2.0 (USB1.1): Windows XP/Vista/7/8</p>  |



| ITEM                               | SPEC   | SPEC IN CHINESE   |
|------------------------------------|--|---|
| <b>(PC)</b>                        |  |   |
| <b>System Requirements (Mac)</b>   | e-SATA: Mac OS 10.4 or above<br>USB2.0 (USB1.1): Mac OS 10.2 or above  | e-SATA: Mac OS 10.4 或更高版本<br>USB2.0 (USB1.1): Mac OS 10.2 或更高版本                         |
| <b>System Requirements (Linux)</b> | e-SATA: Linux 2.4.x or above<br>USB2.0 (USB1.1): Linux Kernel 2.4.x or above   | e-SATA: Linux 2.4.x 或更高版本<br>USB2.0 (向下相容 USB1.1): Linux Kernel 2.4.x 或更高版本             |
| <b>Power Supply</b>                | External Power Adapter<br>Input: AC 100-240V, 50Hz/60Hz<br>Output: DC+12V/3A   | 外接電源供應器<br>Input: AC 100-240V, 50Hz/60Hz<br>Output: DC+12V/3A                           |
| <b>Dimension</b>                   | 147mm x 131mm x 71mm   | 147mm x 131mm x 71mm  |
| <b>Accessories</b>                 | 7928SUSJ-D (hard drives not included)<br>USB 2.0 cable x 1<br>e-SATA cable x 1<br>Power adaptor x 1<br>Power cord x 1<br>User manual x 1 | 7928SUSJ-D (不含硬碟)<br>USB 2.0 傳輸線 x 1<br>e-SATA 傳輸線 x 1<br>電源 x 1<br>電源線 x 1<br>使用手冊 x 1 |
| <b>Weight</b>                      | Product Weight: 535g<br>Gross Weight including Package: 940g<br>Carton N.W: 10.8KGS<br>Carton G.W.: 13.7KGS                              | 產品淨重: 535g<br>產品毛重(含包裝): 940g<br>單箱淨重: 10.8KGS<br>單箱毛重: 13.7KGS                         |
| <b>Carton/Packing</b>              | Retail Box Size: 185 x 120x 210mm<br>Carton Size: 615 x 200x 460mm (10pcs /ctn)  | 彩盒尺寸: 185 x 120x 210mm<br>外箱尺寸: 615 x 200x 460mm (10pcs /箱)                             |

| <b>ITEM</b>    | <b>SPEC</b>  | <b>SPEC IN CHINESE</b>                               |
|----------------|--|--|
| <b>Remarks</b> | Change PC/DUP mode : press the mode button 3 seconds<br>Stop copy : press the start button 3 seconds | 改變 PC/DUP 模式：按住模式按鍵 3 秒進行轉換<br>停止複製：按住開始按鍵 3 秒即可停止複製 |