

SI-9224TB3

Specification



Revision Notice

R.1.0 2017.12.25

Initial release

TABLE OF CONTENTS

| | |
|-----------------------------------|---|
| 1. Appearance | 4 |
| 2. Specification | 4 |
| 3. Features | 5 |
| 4. Operating System Support | 5 |
| 5. Power & Accessories | 5 |

1. Appearance



2. Specification

- A. TBT3 x2
- B. DisplayPort 1.2 x1
- C. M.2 M-key socket x2 (PCIe 3.0 x2)

3. Features

- A. All metal housing.
- B. Compact size 147 x 83 x 47 mm.
- C. Supports 2 x thunderbolt3 40Gbps.
- D. Thunderbolt3 ports support PD 5V@3A 15W power source.
- E. 1 x DisplayPort1.2 for 4K@60Hz output.
- F. 2x M.2 PCIe NVMe SSD inside.
- G. Each SSD transfer rate up to 1500MB/s.
- H. Build soft-raid0 can reach to 2500MB/s.
- I. Fanless.

4. Operating System Support

- A. Mac OS X 10.13.x and future releases.
- B. Windows 7 SP1 32 and 64 bit, Windows 8/10 32 and 64 bit and future releases.

5. Power & Accessories

- A. Including Thunderbolt cable.
- B. External 65W power adapter
- C. User manual x1.
- D. Retail Color Box x1.