

SI-1810SUS3
10 Bay SATA HDD Enclosure
Specification



Detail Spec

| Item | Spec | 繁體中文 | 備註(粗體)或參考寫法 |
|------------------------|--|--|-------------|
| Model No. | SI-1810SUS3 | SI-1810SUS3 | |
| Certifications | CE、FCC、RoHS compliance | 符合 CE、FCC、RoHS 規範 | |
| Color | Black | 黑色 | |
| Material | High quality metal for optimized heat dissipation | 機身採用高質感金屬材質,提升散熱效能 | ◇ |
| HDD Type | 2.5"/3.5" SATA 6G HDD/SSD | 適用 2.5"/3.5"吋 SATA HDD/SSD 硬碟 | |
| Interfaces | 1 x e-SATA (Max. 3Gbps) 1 x USB3.2 (Max. 10Gbps) | 1 x e-SATA (理想值 3Gbps) 1 x USB3.2 (理想值 10G Gbps) | ◇ |
| Tray less | Support | 支援 | |
| Screw less | Support | 支援 | |
| Hot Swappable | NO | 不支援 | |
| Hot Spare | NO | 不支援 | |
| Plug & Play | Support | 支援 | |
| Chipset | JM539B+JM321*3 | JM539B+JM321*3 | |
| RAID Mode | Not support | 不支援 | |
| RAID Setting | Not support | 不支援 | |
| Sleep Mode | USB3.0&2.0&e-SATA without sleep function : 1. The HDD and FAN without idle time sleep function. 2. Take off the cable, the HDD and FAN without sleep function 3. PC sleep, the HDD and FAN without sleep function | USB3.0&2.0&e-SATA 沒有休眠功能: 1. HDD,FAN 沒有限時休眠功能 2. 拔掉 CABLE ,HDD&FAN 不休眠 3. 電腦休眠, HDD&FAN 不休眠 | |
| Rebuild | Not support | 不支援 | |
| Duplicator | Not support | 不支援 | |
| FAN | 140*140*25mm FAN x 1 (1400 rpm) | 140*140*25mm 風扇 x 1(1400 轉/分鐘) | |
| LED Indicator | ● Power LED Blue for power on Read and write purple lights | ● 電源指示燈 電源開啟以藍燈指示/讀寫紫燈 | |

| Item | Spec | 繁體中文 | 備註(粗體)或參考寫法 |
|---------------------|---|---|-------------|
| Features | <ul style="list-style-type: none"> Support up to 10x 2.5"/3.5" SATA 6G HDD/SSD Tool-free and tray-less design Multi-function LED indicators Versatile interface including e-SATA, and USB 3.2 1 silent cooling fans can help HDD dissipation Hard drives individual power supply switch | <ul style="list-style-type: none"> 支援 10 個 2.5"/3.5" SATA 6G HDD/SSD 硬碟 隨拆即用抽取式硬碟安裝設計,無需螺絲固定 多功能 LED 顯示 支援多種高速傳輸介面:e-SATA、USB3.2 內建 1 個高效能靜音風扇,提供最佳的散熱環境 每顆硬碟個別獨立電源開關 | |
| Environment | Operating Temperature: 5°C ~ 35°C Operating Humidity: 20%RH ~ 80%RH Storage Temperature: -20°C ~ 50°C Storage Humidity: 20%RH ~ 80%RH | 適用操作溫度: 5°C ~ 35°C 適用操作濕度: 20%RH ~ 80%RH 適用保存溫度: -20°C ~ 50°C 適用保存濕度: 20%RH ~ 80%RH | |
| Power Supply | Internal universal power supply switch (115V/230V) Input: AC 100-130V/200-260V, 50Hz/60Hz Output: DC +5V/21A +12V/16A (300W) | 可調撥式內建電源 (115V/230V) Input: AC 100-130V/200-260V, 50Hz/60Hz Output: DC +5V/21A +12V/16A (300W) | |
| Dimension | 385*180*330mm(Without feet) | 385*180*330mm(不含腳墊高度) | |
| Accessories | 1810SUSJ3 (hard drives not included) USB3.0 cable x 1 e-SATA cable x 1 Power cord x 1 User manual x 1 Key x 2 | 1810SUSJ3(不含硬碟) USB 3.0 傳輸線 x 1 e-SATA 傳輸線 x 1 AC 電源線 x 1 使用手冊 x 1 硬碟保護鎖 x 2 | |
| Remarks | <ol style="list-style-type: none"> Before you use product, you must make sure switch the correct voltage 115/230V Make sure use 2 HDD at a same time, then the 1810 can work normally. (Slot 1-5 must insert 1 HDD at least, Slot 6-10 must insert 1HDD at least) | <ol style="list-style-type: none"> 使用前請先確定交流電壓, 并調撥至正確的電源伏特數 115 或者 230V 至少同時放入 2 顆 HDD, 1810 才能工作 (槽 1 到 5 至少放 1 顆 HDD, 槽 6 到 10 至少放一顆 HDD) | |